

## ユニファイねじ規格寸法表

呼びサイズ	呼び径		ねじ山数(25.4mmにつき)		ピッチ ミリ換算	引っかかりの 高さ(mm)
	inch	mm	並目	細目		
1/4	0.25	6.35	20		1.27	0.687
				28	0.9071	0.491
5/16	0.3125	7.938	18		1.4111	0.764
				24	1.0583	0.573
3/8	0.375	9.525	16		1.5875	0.859
				24	1.0583	0.573
7/16	0.4375	11.112	14		1.8143	0.982
				20	1.27	0.687
1/2	0.5	12.7	13		1.9538	1.058
				20	1.27	0.687
9/16	0.5625	14.288	12		2.1167	1.146
				18	1.4111	0.764
5/8	0.625	15.875	11		2.3091	1.25
				18	1.4111	0.764
3/4	0.75	19.05	10		2.54	1.375
				16	1.5875	0.859
7/8	0.875	22.225	9		2.82222	1.528
				14	1.8143	0.982
1	1	25.4	8		3.175	1.719
				12	2.1167	1.146
1-1/8	1.125	28.575	7		3.6286	1.964
				12	2.1167	1.146
1-1/4	1.25	31.75	7		3.6286	1.964
				12	2.1167	1.146
1-3/8	1.375	34.925	6		4.2333	2.291
				12	2.1167	1.146
1-1/2	1.5	38.1	6		4.2333	2.291
				12	2.1167	1.146
1-3/4	1.75	44.45	5		5.08	2.75
2	2	50.8	4-1/2		5.6444	3.055
2-1/4	2.25	57.15	4-1/2		5.6444	3.055
2-1/2	2.5	63.5	4		6.35	3.437
2-3/4	2.75	69.85	4		6.35	3.437
3	3	76.2	4		6.35	3.437
3-1/4	3.25	82.55	4		6.35	3.437
3-1/2	3.5	88.9	4		6.35	3.437
3-3/4	3.75	92.25	4		6.35	3.437
4	4	101.6	4		6.35	3.437

※各数値は全て参考値です。万一トラブルが起きても当社では責任を負う事は出来ません

油圧電動空圧等の動力式ボルト締結工具メーカー HYTORC

