

ウィットねじ規格寸法表

呼びサイズ	呼び径 (mm)	ねじ山数 (25.4mmにつき)	ピッチミリ換算	ひっかかり の高さ(mm)
W1/4	6.35	20	1.27	0.813
W5/16	7.94	18	1.41	0.904
W3/8	9.53	16	1.59	1.016
W7/16	11.11	14	1.81	1.162
W1/2	12.7	12	2.12	1.355
W9/16	14.29	12	2.12	1.355
W5/8	15.88	11	2.31	1.479
W3/4	19.05	10	2.54	1.626
W7/8	22.23	9	2.82	1.807
W1	25.4	8	3.18	2.033
W1-1/8	28.58	7	3.63	2.323
W1-1/4	31.75	7	3.63	2.323
W1-3/8	34.93	6	4.23	2.711
W1-1/2	38.1	6	4.23	2.711
W1-5/8	41.28	5	5.08	3.253
W1-3/4	44.45	5	5.08	3.253
W1-7/8	47.63	4-1/2	5.64	3.614
W2	50.8	4-1/2	5.64	3.614
W2-1/4	57.15	4	6.35	4.066
W2-1/2	63.5	4	6.35	4.066
W2-3/4	69.85	3-1/2	7.26	4.647
W3	76.2	3-1/2	7.26	4.647
W3-1/4	82.55	3-1/4	7.82	5.004
W3-1/2	88.9	3-1/4	7.82	5.004
W3-3/4	95.25	3	8.47	5.421
W4	101.6	3	8.47	5.421
W5	127	2-3/4	9.24	5.914

※各数値は全て参考値です。万一トラブルが起きても当社では責任を負う事は出来ません

油圧電動空圧等の動力式ボルト締結工具メーカーHYTORC

